Schlumberger

GEOFRAME PROCESSED INTERPRETATION

Integrated Wireline Log Well Montage

Processed Results

* A Mark of Schlumberger

Using the following logs: CMR*, CNT*, TLD*
AIT*
ECS*, NGT*

COMPANY: Kleinfelder
WELL: CdV-16-3i
FIELD: LANL TA-16 (LANL Characterization and Monitoring Wells)
COUNTY: Los Alamos
STATE: New Mexico
COUNTRY: U.S.
Date Logged: 16-Jan-2004 Date Processed: Jan-04 / May-04
Well Location: Easting: 1,615,808 ft.
Northing: 1,762,600 ft.
Elevations: KB: DF: GL: 7484.00 ft
API Number: Job Number:

FOLD HERE The well name, location, borehole reference data were furnished by the customer.

All interpretations are opinions based on inferences from electrical or other measurements and we cannot, and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretations made by any of our officers, agents or employees. These interpretations are also subject to Clause 4 of our General Terms and Conditions as set out in our current Price Schedule.

Field Recording:	Location: Farmington	Software Version: 11C0-305	Engineer: T. Hansen & A. Whitten
Office Recording:	ICS Center: SWS Sacramento	Baseline: GF3.8.1	Log Analyst: Ned Clayton

Mud and Borehole Measurements:

Rm @ Measured temperature:	@	BHT: 63.0 degF	Bitsize: 12.25 in
Rmf @ Measured temperature:	@	Type Fluid in Hole	Air / Drilling Foam
Rmc @ Measured temperature:	@	Mud Density:	

Remarks:

AIT-NGT tool run serves as primary depth reference.
No water in borehole at time of logging (except possibly below 1392 ft. below surface).
ELAN* performed with some mineral constraints based on XRD lab analysis of LANL Tuffs.
Processed logs do not clearly indicate any significant zones with full water saturation.